

12.1 inch WIDE PANEL MOUNT LCD MONITOR

ORDERING INFORMATION

121WPAA-1280 VGA/ Video x 1/ S-Video/ Audio x 1/ 5-wires Touch Screen
 121WPAB-1280 VGA/ Video x 1/ S-Video/ Audio x 1
 121WPAC-1280 VGA/ 5-wires Touch Screen / Speaker
 121WPAD-1280 VGA/ Speaker
 121WPAC-1280-DVI VGA/ DVI/5-wires Touch Screen / Speaker
 121WPAD-1280-DVI VGA/ DVI/ Speaker

ORDERING INFORMATION

Digital Signage
 Self-service Terminal
 Public Information Display
 Instrumentation
 Hospitality
 In-vehicles and transportation
 Resistive Touch Option
 Sunlight Readable LED BL 1000 cd/m² Option



SPECIFICATION

Panel	Cell Type Pixel Arrangement Glass Surface Pixel number Pixel Pitch Display Size Active Area Color Depth Light Source Brighness Contrast Ratio Viewing Angle	Color active matrix TFT (Thin-Film-Transistor) LCD panel RGB vertical stripe Anti-Glare coating 1280(H) x 800(V) 0.204(H) x 0204(V) mm 12.1" wide viewable diagonal area 261.12(H) x 163.2(V) mm 262K colors Long life, 50,000 hrs (typ) 450 cd/m ² (typ) 4 CCFL 350 : 1 horizontal(typ) (L ~ R : - 70o ~ +70o) vertical (typ) (U ~ D : - 65o ~ + 65o)
Input Signal	Video Sync Frequency	Analog RGB (0.7/1.0 Vp-p, 75 ohms) Composite Sync, Fh : 30 - 82Khz , Fv : 60 -75Hz
Resolution	Supported Recommended	1280 x 800@60 / 70 / 75 Hz 1024 x 768@60 / 70 / 75 Hz 800 x 600@60 / 70 / 75 Hz 640 x 480@60 / 70 / 75 Hz 640 x 350@ 70 Hz 1280 x 800@60 Hz
Control	Front Panel Winsticker (OSD)	Power , Menu,Select , + (Inc) , - (Dec) , Auto Adjust, Brightness, Contrast, H-Position, V-Position Phase, Color, Default,Volume , Language, Memory Recall
Power	Input Voltage	AC: 90 to 260VAC, 50 / 60 Hz DC:12V/ 3A
Power Rating	Operation Off	30 watt < 5 watt
Audio	Operating Condition Temperature Humidity	2W x 1 Speaker -10 ~ 65 10% ~ 90% (no condensation)
Storage Condition	Temperature Humidity	- 30 ~ 70 10% ~ 90% (no condensation)
Dimensions	Physical	264 x 225 x 40.5 mm (W x H x D)
Weight	N.W. / G.W.	Kg /Kg
Options	Video-In Touch Screen	1x RCA-Connector 1xS-Video 5-wires Resistive type, USB Interface
Certification		FCC, CE