

INDUSTRIAL DISPLAY MONITOR ALUMINUM FRONT PANEL MEET IP65

10.4"



AL104

Panel	Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD panel
	Pixel Arrangement	RGB vertical stripe
	Glass Surface	Anti-Glare coating
	Pixel number	800(H) x 600(V)
	Pixel Pitch	0.264(H) x 0.264(V) mm
	Display Size	10.4" viewable diagonal area
	Active Area	211.2(H) x 158.4(V) mm
	Color Depth	262K colors
	Light Source	Long life, 50,000hrs (typ)
	Brighness	350 cd/m ² (typ)
	Contrast Ratio	300 : 1
	Viewing Angle	horizontal(typ) (L ~ R : -50o ~ +50o) vertical (typ) (U ~ D : -35o ~ +35o)
	Input Signal	Video
Sync		Composite Sync,
	Frequency	Fh : 30- 82Khz , Fv : 60-75Hz
Resolution	Supported	1024 x 768@60/ 70 /75 Hz 800 x 600@60/ 70 /75 Hz 640 x 480@60/ 70 /75 Hz 720 x 400@60/ 70 Hz 640 x 350@70 Hz
	Recommended	800 x 600@60Hz
Control	Front Panel	Power , Menu,Select, + (Inc), - (Dec), Auto Adjust, Brightness, Contrast, H-Position, V-Position
	Winsticker (OSD)	Phase, Color, Default,Volume, Language, Memory Recall
Power	Input Voltage	AC: 90 to 260VAC, 50 /60 Hz DC:12V/3A
	Power Rating	Operation 25 watt Off < 5 watt
Audio		2W x 1 Speaker
	Operating Condition	Temperature -10 ~ 65 Humidity 10% ~ 90% (no condensation)
Storage Condition	Temperature	- 30 ~ 70
	Humidity	10% ~ 90% (no condensation)
Dimensions	Physical	264 x 225 x 40.5 mm (W x H x D)
	Weight	N.W. /G.W. Kg /Kg
	Options	1x RCA-Connector 1xS-Video 5-wires Resistive type, USBor RS-232 Interface
	Touch Screen	
Certification		FCC, CE

FEATURES

- Aluminum front panel meet IP65 standard
- Analog VGA and DVI input interfaces support
- Optional S-video and RCA
- Optional upport 9~36VDC power input for mobile application
- USB or RS-232 interface touch screen
- Anti-Glare Tampered glass
- Optional 5-Wire Resistive Touch Sensor
- RoHS Compliance
- Support Wall/Rack/Arm/Panel/ VESA 75 mount
- Chassis Color Silver OR Black

ORDERING INFORMATION

- AL104-8060 VGA / Audio x 1
- AL104-8060-XX-X
- XX
- V with S-Video & RCA
- DVI with DVI
- 5W with 5 wire Touch Sensor
- WI with Wide input PSU
- X
- B Black
- S Silver

- With POS STAND -PS
- With Normal STAND -NS

ACCESSORIES

- *VGA Cable
- *DVI Cable
- *S-Video Cable
- *RCA Cable
- *Universal / Auto-Sensing, 90 to 260V AC
- *Touch Panel Driver CD
- *User Manual

AL104 MECHANICAL DRAWING

