


CSM-7011A1

Color TFT LCD Monitor




INSTRUCTION MANUAL

APPEARANCE



OUTLINE



SPECIFICATIONS

DISPLAY	7" COLOR TFT LCD
RESOLUTION	1440(H) x 234(V)
ACTIVE AREA	150.08(W) x 86.58(H)
BACK LIGHT	LED
INPUT SIGNAL	NTSC & PAL (auto-switch) composite video signal 1 Vp-p / 75 ohm sync. Negative
LAMP LIFE	30,000 hr min. (at Tamb = 25 °C)
POWER SOURCE	DC 10V ~ 17V (ripple 0.5 Vp-p max.)
POWER CONSUMPTION	4.5W max.
BRIGHTNESS	400 nit TYP.
CONTRAST	350 TYP.
VIEWING ANGLE	TOP 35 deg. BOTTOM 50 deg. LEFT/RIGHT 60 deg.
OPERATING TEMPERATURE	-30 °C ~ 80 °C
STORAGE TEMPERATURE	-40 °C ~ 85 °C
OPERATING HUMIDITY	85% RH max.
STORAGE HUMIDITY	85% RH max.
OVERALL DIMENSIONS	106(H) x 193(W) x 24.9(D)
WEIGHT	320 g


FUNCTIONS

PICTURE ADJUSTMENT

- BRIGHT
Press UP or DOWN directly to adjust brightness.



- COLOR / CONTRAST / DIMMER
To press MENU, the screen will appear COLOR / CONTRAST / DIMMER / BRIGHT in turn, and then press UP or Down to to adjust the picture quality.



ATTACHMENT

- CABLE
Length : 140 cm



- CABLE
Length : 30 cm



- BRACKET : P/N : ST-014 "



CAUTION

1. Don't expose to direct sunlight. (refer to specification)
2. Don't expose temperature extremes. (refer to specification)
3. Avoid dropping and strong impact.
4. Avoid wet and dust.
5. Never attempt to take apart and maintain by yourself.