

# 10.4 inch SVGA Open Frame LCD Monitor

## APPLICATION

ATM  
 Self-service Terminal  
 KIOSK  
 Public Information Display  
 Instrumentation  
 Hospitality  
 In-vehicles and transportation  
 Resistive,SAW,Capacitive,IR Touch Option  
 High Brightness 600 cd/m2 Option  
 LED BL 400 cd/m2 Option



## ORDERING INFORMATION

- a. OF104AA-8060 VGA / Video x 1 / S-Video / Audio x 1 / 5-wires resistive
- b. OF104AB-8060 VGA / Video x 1 / S-Video / Audio x 1
- c. OF104AC-8060 VGA / 5-wires resistive Touch / Speaker
- d. OF104AD-8060 VGA / Speaker
- e. OF104AC-8060-DVI VGA / DVI / 5-wires resistive Touch / Speaker
- f. OF104AD-8060-DVI VGA / DVI / Speaker
- g. OF104AC-8060-S VGA / Surface Acoustic Wave Touch / Speaker
- h. OF104AC-8060-C VGA / Surface Capacitive Touch / Speaker
- i. OF104AC-8060-DVI-S VGA / DVI / Surface Acoustic Wave Touch / Speaker
- j. OF104AC-8060-DVI-C VGA / DVI / Surface Capacitive Touch / Speaker

## SPECIFICATION

<b>Panel</b>	Cell Type Pixel Arrangement Glass Surface Pixel number Pixel Pitch Display Size Active Area Color Depth Light Source Brighness Contrast Ratio Viewing Angle	Color active matrix TFT (Thin-Film-Transistor) LCD panel RGB vertical stripe Anti-Glare coating 800(H) x 600(V) 0.264(H) x 0.264(V) mm 10.4" viewable diagonal area 211.2(H) x 158.4(V) mm 262K colors Long life, 50,000hrs (typ) 350 cd/m <sup>2</sup> (typ) 300 : 1 horizontal(typ) (L ~ R : - 50o ~ +50o) vertical (typ) (U ~ D : -35o ~ + 35o)	<b>Control</b>	Panel Winsticker (OSD) Power , Menu,Select, + (Inc) , - (Dec) , Auto Adjust, Brightness, Contast, H-Position, V-Position Phase, Color,Default,Volume , Language, Memory Recall
<b>Input Signal</b>	Video Sync Frequency	Analog RGB (0.7/1.0Vp-p, 75 ohms) Composite Sync, Fh : 30 -82Khz , Fv : 60 -75Hz	<b>Power</b>	<b>Input Voltage</b> AC: 90 to 260VAC, 50 / 60Hz DC:12V/ 1.2A
<b>Resolution</b>	Supported          Recommended	1024 x 768@60/ 70 / 75Hz 800 x 600@60/ 70 / 75Hz 640 x 480@60/ 70 / 75Hz 720 x 400@60/ 70 Hz 640 x 350@ 70 Hz 800 x 600@60Hz	<b>Power Rating</b>	<b>Operation</b> 25 watt <b>Off</b> < 5 watt
			<b>Audio</b>	<b>2W x 1 Speaker</b>
			<b>Operating Condition</b>	<b>Temperature</b> -10 ~ 65 <b>Humidity</b> 10% ~ 90% (nocondensation)
			<b>Storage Condition</b>	<b>Temperature</b> - 30 ~ 70 <b>Humidity</b> 10% ~ 90% (nocondensation)
			<b>Dimensions</b>	<b>Physical</b> (W x H x D)
			<b>Weight</b>	N.W. /G.W. 3Kg /4Kg
			<b>Options</b>	Video-In 1x RCA-Connector 1xS-Video Touch Screen USB,RS-232 Interface
			<b>Certification</b>	FCC, CE

## MECHANICAL DRAWING

