

17 inch Wide Open Frame LCD Monitor

FEATURES

**KIOSK, Equipment
Self-service Terminal
Gaming
Digital Signage
Public Information Display
Instrumentation
Hospitality**
Resistive, SAW, Capacitive, IR Touch Option



ORDERING INFORMATION

- OF170WAA-1276 VGA / Video x 1 / S-Video / Audio x 1 / 5-wires resistive
- OF170WAB-1276 VGA / Video x 1 / S-Video / Audio x 1
- OF170WAC-1276 VGA / 5-wires resistive Touch / Speaker
- OF170WAD-1276 VGA / Speaker
- OF170WAC-1276-DVI VGA / DVI / 5-wires resistive Touch / Speaker
- OF170WAD-1276-DVI VGA / DVI / Speaker
- OF170WAC-1276-S VGA / Surface Acoustic Wave Touch / Speaker
- OF170WAC-1276-C VGA / Surface Capacitive Touch / Speaker
- OF170WAC-1276-DVI-S VGA / DVI / Surface Acoustic Wave Touch / Speaker
- OF170WAC-1276-DVI-C VGA / DVI / Surface Capacitive Touch / Speaker

SPECIFICATION

Panel	Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD panel
	Pixel Arrangement	RGB vertical stripe
	Glass Surface	Anti-Glare coating
	Pixel number	1280(H) x 768(V)
	Pixel Pitch	0.28875(H) x 0.28875(V) mm
	Display Size	17" Wide viewable diagonal area
	Active Area	369.6(H) x 221.76(V) mm
	Color Depth	16.2M colors
	Light Source	Long life, 50,000 hrs (typ)
	Brightness	350 cd/m ² (typ)
	Contrast Ratio	600 : 1
	Viewing Angle	horizontal (typ) (L ~ R : - 85o ~ +85o) vertical (typ) (U ~ D : - 85o ~ + 85o)
Input Signal	Video	Analog RGB (0.7/1.0Vp-p, 75 ohms)
	Sync	Composite Sync,
	Frequency	Fh : 30 - 82KHz, Fv : 60 - 75Hz
Resolution	Supported	1280 x 768@60 / 75 Hz 1024 x 768@60 / 70 / 75 Hz 800 x 600@60 / 70 / 75 Hz 720 x 400@60 / 70 Hz 640 x 350@ 70Hz
	Recommended	1280 x 768@60 Hz

Control	Panel	Power , Menu, Select, + (Inc) , - (Dec) , Auto Adjust, Brightness, Contrast, H-Position, V-Position Winsticker (OSD) Phase, Color, Default, Volume , Language, Memory Recall
Power	Input Voltage	AC: 90 to 260VAC, 50 / 60Hz DC: 12V / 1.2A
Power Rating	Operation	40 watt
	Off	< 5 watt
Audio	2W x 1 Speaker	
Operating Condition	Temperature	-10 ~ 65
	Humidity	10% ~ 90% (no condensation)
Storage Condition	Temperature	- 30 ~ 70
	Humidity	10% ~ 90% (no condensation)
Dimensions	Physical	(W x H x D)
Weight	N.W. / G.W.	4Kg / 5Kg
Options	Video-In	1x RCA-Connector 1x S-Video
	Touch Screen	USB, RS-232 Interface
Certification	FCC, CE	

MECHANICAL DRAWING

